

Wassar 550

自動洗衣機

Automatic Washing Machine



- 大直徑內膽設計，特別適用於對牛仔，休閒服，風雨衣等厚料衣物進行石洗和酵洗
- 前置式結構，水比小，配合變頻調速，滿足多種洗滌要求，降低洗衣成本
- 機身可傾斜，自動卸料
- 采用PLC可編程控制器控制及人性化操作界面觸摸顯示屏操作，可記憶30組洗衣程式，每組程式可設置30個步驟
- 采用蒸汽直接加熱，即時/到溫計時選擇
- 本機標配一套電控氣動入水系統，配合流量計可準確控制水位(另可選購一套電控氣動入水系統)
- 配有手動加藥系統
- 不帶脫水功能，用戶可選購本公司NS-2500系列工業脫水機配合使用

選購件：

鹽水配量缸連輸送系統-200L
藥水配量缸-100L
自動入藥水系統-100L
電控氣動入水系統(工作溫度：-20~80°C)
另增氣動排水系統 - Ø8"
外置式間接熱交換器系統
VaporTec 200 納米霧化系統

- Large diameter inner drum, especially suitable for stone wash and enzyme wash of thick garment such as jeans, casual wear, coat, etc.
- Front loading structure, lower water ratio, and variable frequency speed control can satisfy the requirements of various washes with lower cost
- Tiltable machine body for automatic garment unloading
- Adopt PLC and human friendly touch screen for operation; it can memorize 30 groups of programs, each of which can set up to 30 steps
- Heating directly by steam; users can select immediate or up-to temperature timing
- With one set of electric controlled pneumatic water feeding system as standard configuration in conjunction with flowmeter for accurate water level control(additional one set of electric controlled pneumatic water feeding system can be purchased as an option)
- With manual chemical feeding system
- Without extracting function. Users could purchase NS-2500 series industrial extractor to work in combination with this machine

Options:

Salt dosing tank with feeding system -200L
Chemical dosing tank-100L
Automatic chemical feeding system-100L
Electric controlled pneumatic water feeding system (working temperature: -20~80°C)
Optional pneumatic water draining system - Ø8"
External indirect heat exchange system
VaporTec 200



單排水系統
Single water draining system



齒輪驅動系統
Gear driving system of



可傾斜卸料系統
Tilting unloading system

選購件 Options:




O-I-21-04-200
鹽水配量缸連輸送系統-200L
Salt dosing tank with
feeding system-200L



O-I-21-03-100
藥水配量缸-100L
Chemical dosing tank-100L



O-I-21-02-100
自動入藥水系統-100L
Automatic Chemical
Feeding System-100L



O-I-04-3-1
電控氣動入水系統 - Ø3"
Electric Controlled Pneumatic
Water Feeding System - Ø3"



O-I-82-01另增氣動排水系統 - Ø8"
Optional pneumatic water draining
system - Ø8"



O-I-52-06
外置式間接加溫系統
External indirect heating system



VaporTec 200
納米霧化系統

型號 Model	容量(kg) Capacity	內膽容積(m³) Inner Drum Volume	電源 Power Supply	馬達功率 (kW) Motor Power	內膽尺寸(mm) Inner Drum Size	外膽尺寸(mm) Outer Drum Size	洗滌速度(RPM) Washing Speed	機身尺寸(mm) Machine Size
Wassar 550	500	5	3PH/380V/50Hz	18.5	Ø1980x1640x4	Ø2085x1905x3	12~38	3200x3210x2620



藝誠(余氏)發展有限公司
Ngai Shing Development Limited

香港九龍長沙灣永康街52號地下

G/F., 52 Wing Hong St.,

Cheung Sha Wan, Kln., Hong Kong.

Tel:(852)2741 9981, 2742 0078 E-MAIL:info@ngaishing.com
Fax:(852)2785 3149 Http://www.ngaishing.com

