


NS-347E

自動電加熱式蒸汽鍋爐

Automatic Electric Steam Boiler



NS-347E-24

- 電鍋爐採用全自動運行，節省人員管理成本
 - 完善的全自動控制系統，自動給水、自動加熱、操作簡單、安全性高
 - 採用低水位斷電系統設計，避免無水空燒
 - 鍋爐體積小，安裝方便、簡單
 - 根據不同的熨斗規格或蒸汽使用設備選擇相應的蒸汽鍋爐，以滿足熨燙、加熱或其它需求
- Automatically-operated electric heated boiler, saving manpower
 - With perfect control system, water feeding and heating are fully automated; easy operation and high safety
 - Automatic power off when water level drops below lower limit, preventing boiler from dry burning
 - Small size, easy and simple installation
 - Based on iron specification or steam-consuming equipment, users can choose the fittest among many different models to meet their requirements of ironing, heating, etc.

型號 Model	電源 Power Supply	發熱線功率(kW) Heater Power	儲水箱容量(L) Capacity of Water Tank	蒸汽量(kg/h) Steam Capacity	可支持電熨斗數(pcs) Max. Number of Electric Steam Iron to Support	可支持全蒸汽熨斗數(pcs) Max. Number of Steam Heated Iron to Support	淨重(kg) Net Weight	裝箱尺寸(mm) Packing Size
NS-347E-6	3PH/380V/50Hz	6	11	9	2	1	80	620x440x1050
NS-347E-9		9		13.5	3	2		
NS-347E-12		12	17	18	4	3	105	680x440x1140
NS-347E-18		18		27	7	5		
NS-347E-24		24	21	36	9	7	135	840x620x1100
NS-347E-36		36		54	14	10		
NS-347E-48		48	29	72	19	14	160	820x630x1200
NS-347E-72		72		108	28	21		
NS-347E-108		108	87	162	43	32	295	970x760x1550



藝誠(余氏)發展有限公司
Ngai Shing Development Limited

香港九龍長沙灣永康街52號地下

G/F., 52 Wing Hong St.,

Cheung Sha Wan, Kln., Hong Kong.

Tel : (852) 2741 9981, 2742 0078

Fax: (852) 2785 3149

E-MAIL: info@ngaishing.com

Http://www.ngaishing.com