
## **NS-5503**


## 側袖摺熨機

## **Sleeve Placket Folding and Ironing Machine**









- 適用於梳織、針織側袖摺熨
- 采用PLC可编程控制器控制及人性化操作界面觸摸 顯示屏操作
- 鐳射光線輔助對齊、定位
- 下模備有抽風功能,有助物料定型
- 前進前出式設計,方便取料,提高工作效率;自動 收料疊放於操作者前,取料快捷方便
- 更換下模容易,可裝配不同尺碼的側袖成型模
- 跟機模可摺側袖寬度為1",訂造模可摺側袖寬度範 圍3/4"~11/4"

跟機模:1"萬能模

選購模:各種規格側袖貼模,可摺寬度有: 3/4",

7/8" , 1" , 1 1/8" , 1 1/4"

- Suitable for folding and pressing sleeve placket of woven and knitted fabrics
- Adopt PLC and user friendly touch screen for operation
- With laser marker to assist aligning and positioning
- Lower mould with vacuuming function to facilitate shaping
- Front-in and -out design, easy material collecting and high efficiency. Collected material will be automatically stacked in front of the operator for pick-up
- Easy lower mould changing; different sized sleeve placket forming mould available for selection
- Standard mould: folding width 1"; customized mould: folding width between  $\frac{3}{4}$ " ~1  $\frac{1}{4}$ "

Standard: 1" universal mould

Options: Sleeve placket mould of various folding width, including 3/4", 7/8", 1", 1 1/8" & 1 1/4"



下模抽風便於將裁片折邊、貼合完好 Vacuuming of lower mould facilitates folding and flattening fabric piece



自動收料於操作者前方,取料便捷 Automatic stacking in front of the operator, easy to collect the sleeve plackets

**跟機模:**1"萬能模(包含以下1.2.3.模型)

Standard: 1" universal mould (including below moulds 1~3)

1. 三尖貼底斜角模(AC-C-3-6-3)

Bottom Inclined Triangular Sleeve Placket Mould



2. 三尖貼底方型模(AC-C-3-7-3)

Bottom Squared Triangular Sleeve Placket Mould



3.四方三尖側貼模(AC-C-3-8-3) Square Sleeve Placket Mould




三尖貼底斜角側袖摺熨效果相

Appearance of Bottom Inclined Triangular Sleeve Placket




三尖貼底方型側袖摺熨效果相 Appearance of Bottom Squared Triangular Sleeve Placket



四方三尖側貼摺熨效果相 Appearance of Square Sleeve Placket





此兩件擋板適合3/4"~11/8"的萬能模安裝(已裝機)

These two plates are suitable for the installation of 3/4" ~ 1 1/8" complete set of mould (mounted on machine)



此兩件擋板適合11/8"~11/4"的萬能模安裝(跟機件) These two plates are suitable for the installation of 1 1/8" ~ 1 1/4" universal mould (standards)

型號	電源	總功率(kW)	壓縮空氣壓力(kg/cm²)	耗壓縮空氣量(L/min)	生產量(對/小時)	淨重(kg)	機身尺寸(mm)
Model	Power Supply	Total Power	Compressed Air Pressure	Compressed Air Consumption	Output (pair/hr)	Net Weight	Machine Size
NS-5503	3PH/380V/50Hz	7.4	5	40	135	323	920×1340×1620



## 藝誠(余氏)發展有限公司 Ngai Shing Development Limited

香港九龍長沙灣永康街52號地下 G/F.,52 Wing Hong St., Cheung Sha Wan,Kln.,Hong Kong. 1, 2742 0078 E-MAIL:info@ngaishing.com

Tel:(852)2741 9981, 2742 0078 Fax:(852)2785 3149

Http://www.ngaishing.com