

NS-81P-L-2 自動切領咀反領焗領機


Automatic Collar Trimming, Turning and Blocking Machine



切領咀、反領操作
Collar tip trimming and turning



機械夾夾緊領
Automatic clamp fixing collar



機械夾自動收料
Automatic stacking clamp

- 適用於切領咀、反領、焗領功能
- 採用單片微處理器控制及人性化觸摸顯示屏操作
- 採用電加熱及獨立數字溫度控制器控制溫度
- 下模有定位頂針選擇開關，以滿足不同布料需求
- 具有特長的壓領模
- 採用機械夾固定領，左邊機械手輔助收料，減少人工操作
- 生產效率高，每8小時產量可達1800條領
- 已安裝跟機切刀：C33-00117-3-V1 88°中間刀

選購件：

C33-00117-1 75°中間刀， C33-00117-3-V1 88°中間刀，
C33-00117-4-V1 105°中間刀

- Suitable for collar tip trimming, turning and blocking
- Adopt single chip microprocessor for control and user friendly touch screen for operation
- Electric heated design with independent digital thermostat for temperature control
- Lower mould has selector switch for ejector pin to cater for the requirement of different fabrics
- Ultra long collar pressing mould
- With automatic clamp to fix collar and manipulator on the left side to collect material, it can reduce a lot manual operation
- High production efficiency: it could finish 1800pcs of collars every 8 hours
- **Installed standard cutter:** C33-00117-3-V1 88° cutter
- **Optional Accessories :**
C33-00117-1 75° cutter, C33-00117-3-V1 88° cutter,
C33-00117-4-V1 105° cutter

型號 Model	電源 Power Supply	總功率(kW) Total Power	發熱線功率(kW) Heater Power	壓領最長(inch) Max. Pressing Length	壓縮空氣壓力(kgf/cm ²) Compressed Air Pressure	耗壓縮空氣量(L/min) Compressed Air Consumption	機身尺寸(mm) Machine Size
NS-81P-L-2	1PH/220V/50Hz	2.8	2.6	10 ½	5	46.8	1310x950x1250*



藝誠(余氏)發展有限公司
Ngai Shing Development Limited

香港九龍長沙灣永康街52號地下

G/F., 52 Wing Hong St.,

Cheung Sha Wan, Kln., Hong Kong.

Tel: (852) 2741 9981, 2742 0078
Fax: (852) 2785 3149

E-MAIL: info@ngaishing.com
Http://www.ngaishing.com