

NS-2500-55 / 130 / 200 / 260

工業脫水機連電子變速及時間剎車

**Industrial Extractor with Frequency Speed Control and Timer
Brake Stop**



NS-2500-260



- 適用於洗水漂染廠衣物脫水
- 脫水時間可調(1~99分鐘)
- 具有氣動開門功能，提高工作效率
- 備氣動剎車，能快速停止內膽慣性轉動
- 懸浮式避振裝置，有效降低機器運轉時產生的振動
- 過震保護裝置，當內膽衣物分佈不均，產生震動幅度過大時，過震保護裝置將停止內膽轉動
- 變頻器控制內膽轉速，有三段速度和無極速度兩種選擇，不會使衣物過干，造成皺紋
- 本機有噪音小，工作穩定，性能可靠等優點
- 帶有轉速顯示屏，便於操作
- 內膽採用SUS 304不鏽鋼
- Suitable for washed or dyed garment water extraction in industrial washing industries
- Extracting time is adjustable (1-99 minutes)
- With pneumatic door opening function for high work efficiency
- Equipped with pneumatic brake so as to stop inertial movement of the inner drum immediately
- Suspension anti-vibration system for minimizing vibration during running
- Over-vibration protection device, when the distribution of garments inside inner drum is uneven and the vibration amplitude is beyond limit, the vibration protection device will stop the inner drum from spinning
- With inverter control for inner drum spinning speed and it has two options: three-step speed and stepless speed, which can prevent garments from being over dried so as to avoid dead wrinkles
- The machine featured low noise, high stability and reliability, etc.
- With spinning speed display screen, convenient for operation
- Adopts SUS 304 stainless steel for inner drum

型號 Model	容量 (lbs) Capacity	電源 Power Supply	總功率(kW) Total Power	最高脫水速度 (RPM) Max. Spinning Speed	壓縮空氣壓力 (kgf/cm ²) Compressed Air Pressure	耗壓縮空氣量(L/min) Compressed Air Consumption	內膽尺寸 (mm) Inner Drum Size	機身尺寸 (mm) Machine Size
NS-2500-55	55	3PH/380V/50Hz	3	1200	5	0.25	Ø635 × 290	1350 × 1040 × 850
NS-2500-130	130		5.5	1060		2.65	Ø915 × 360	1770 × 1260 × 950
NS-2500-200	200		7.5	940		2.65	Ø1067 × 360	2060 × 1580 × 1060
NS-2500-260	260		11	810		2.65	Ø1220 × 380	2300 × 1740 × 1100



藝誠(余氏)發展有限公司
Ngai Shing Development Limited

香港九龍長沙灣永康街52號地下

G/F., 52 Wing Hong St.,

Cheung Sha Wan, Kln., Hong Kong.

Tel : (852) 2741 9981, 2742 0078

Fax: (852) 2785 3149

E-MAIL: info@ngaishing.com

Http://www.ngaishing.com