

NS-8404P-A

自動立體擔桿壓平機

Automatic 3D Yoke Pressing Machine



- 適用於襯衫立體擔桿粘合壓熨
- 採用PLC可編程控制器控制及人性化觸摸顯示屏操作
- 垂直加壓方式，壓力分佈均勻，壓熨更平整
- 微壓、輕壓、脈沖、重壓四種壓熨方式供選擇設定，可滿足不同面料需求
- 上模加熱採用三個獨立數字式溫度控制器控制，溫度更控制精確
- 全新的模具結構設計，採用兩組立體擔桿模，無需調節模具位置，即可滿足不同形狀和尺寸的前後立體擔桿同時壓熨
- 下模氣袋配合耐壓的高溫硅膠條，可消除擔桿壓熨時擔桿縫與摺位的厚薄偏差，達到最佳壓熨效果
- 獨立真空抽濕泵，有助衣物定位、冷卻，定型效果佳

- Suitable for fusing press of shirt 3D yoke
- Adopt PLC and user friendly touch screen for operation
- Vertical pressing offers uniform pressure distribution with smoother effect
- Four pressing modes for select: slight press, light press, pulse, and heavy press, to cater for various fabrics
- Equipped with 3 independent digital thermostats for accurate temperature control of upper mould heating
- A brand new mould structure design, using two sets of 3D yoke moulds, can meet the simultaneous hot pressing needs of front and rear 3D yokes of different patterns and sizes without adjusting the mould position
- Lower mould air bag works in coordination with high temperature & pressure proof silicone rubber to offset thickness difference between yoke seam and folding position, thereby to achieve the optimum pressing effect
- Independent vacuum pump to facilitate garment positioning, cooling and setting

型號 Model	電源 Power Supply	總功率(kW) Total Power	發熱線功率(kW) Heater Power	真空泵功率(kW) Vacuum Pump Power	壓縮空氣壓力(kgf/cm ²) Compressed Air Pressure	耗壓縮空氣量(L/min) Compressed Air Consumption	平均粘合壓力(kgf/cm ²) Average Fusing Pressure	機身尺寸(mm) Machine Size
NS-8404P-A	3PH/380V/50HZ	4.3	3.15	1.1	5	296	2.5	1140x800x2130



藝誠(余氏)發展有限公司
Ngai Shing Development Limited

香港九龍長沙灣永康街52號地下

G/F., 52 Wing Hong St.,

Cheung Sha Wan, Kln., Hong Kong.

Tel : (852) 2741 9981, 2742 0078

Fax : (852) 2785 3149

E-MAIL: info@ngaishing.com

Http://www.ngaishing.com